



ANTI-X

Our original anti-static vacuums. Safe for use in all combustible dust environments. Tested by an OSHA-approved laboratory, these vacuums are completely bonded and grounded to prevent against any static electricity buildup, eliminating the risk of a spark.



	HV-30-1520-X	HV-30-1560-X	HV-30-1510-X	HV-30-15185-X	HV-30-2010-X	HV-30-20185-X	HV-55-1520-X	HV-55-1560-X	HV-55-1510-X	HV-55-15185-X	HV-55-2010-X	HV-55-20185-X
Drum Size	30 Gallon	30 Gallon	30 Gallon	30 Gallon	30 Gallon	30 Gallon	55 Gallon	55 Gallon	55 Gallon	55 Gallon	55 Gallon	55 Gallon
Assembled Dimensions	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"
Compressed Air CFM	20	45	85	170	85	170	18	45	85	170	85	170
Minimum HP Required	5	12	25	50	25	50	5	12	25	50	25	50
Compressed Air Hose Minimum Diameter	1/2"	1/2"	3/4" recommended	3/4"	3/4"	3/4"	1/2"	1/2"	3/4" recommended	3/4"	3/4"	3/4"
Compressed Air Hose Type	Black Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire	Standard Rubber with Grounding Wire
Vacuum Hose Diameter	1 1/2"	1 1/2"	1 1/2"	1 1/2"	2"	2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	2"	2"
Max Vacuum Hose Length	12'	25'	50'	100'	50'	100'	12'	25'	50'	100'	50'	100'
Vacuum Hose CFM	45	75	140	290	140	290	45	75	140	290	140	290
Hose Type	Anti-Static Grounded											
Vacuum Suction Pressure	8" Hg	16" Hg	18" Hg	20" Hg	18" Hg	18" Hg	13" Hg	16" Hg	18" Hg	18" Hg	18" Hg	18" Hg
Filter Type / Micron Size	Optional HEPA Available											
S³HUSH SILENCER	76	77	78	77	78	77	76	77	78	80	78	80
Shipping Weight (lbs)	120	120	120	135	130	145	120	120	120	135	130	145