HAFCOVAC

CERTIFIED PNEUMATIC VACUUMS

EXL

Our **EXL Vacuums** are the top of the line HafcoVac option. **ATEX Certified Vacuums** are the safest vacuum for use in combustible dust environments. Division 1: Groups A, B, C, D T6, Class II, Division 1: Groups E, F, G T6. The Atex Certification guarantees a completely anti-static vacuum unit, with no potential for sparking. In addition, the ATEX EXL units come with a pre-installed silencer, reducing the sound pressure level by at least 80 percent, while maintain full performance.

ATEX II 2 D

Equivalent to National Fire Protection Associati

Class I Division 1*	Groups A, B, C, D T6
Class II Division 1	Groups E, F, G T6

*Zone 1 Only

CERTIFIED OSHA COMPLIANT LIFETIME WARRANTY

MADE IN THE *USA*

NFPA®

	HV-30-1520-EXL	HV-30-1560-EXL	HV-30-1510-EXL	HV-30-15185-EXL	HV-30-2010-EXL	HV-30-20185-EXL	HV-55-1520-EXL	HV-55-1560-EXL	HV-55-1510-EXL	HV-55-15185-EXL	HV-55-2010-EXL	HV-55-20185-EXL
Drum Size	30 Gallon	30 Gallon	30 Gallon	30 Gallon	30 Gallon	30 Gallon	55 Gallon	55 Gallon	55 Gallon	55 Gallon	55 Gallon	55 Gallon
Assembled Dimensions	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	39"H x 25" x 20"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"	46"H x 26" x 24"
Compressed Air CFM	20	45	85	170	85	170	20	45	85	170	85	170
Minimum HP Required	5	12	25	50	25	50	5	12	25	50	25	50
Compressed Air Hose Minimum Diameter	½"	½"	¾"	¾"	¾"	¾"	½"	½"	¾"	¾"	¾"	¾"
Compressed Air Hose Type	Black Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire	Rubber with Grounding Wire
Vacuum Hose Diameter	1½"	1½"	1½"	1½"	2"	2"	1½"	1½"	1½"	1½"	2"	2"
Max Vacuum Hose Length	12'	25'	50'	100'	50'	100'	12'	25'	50'	100'	50'	100'
Vacuum Hose CFM	45	75	90	170	100	190	45	75	90	170	100	190
Hose Type	ATEX rated with Grounding Wire											
Vacuum Suction Pressure	13" Hg	16" Hg	18" Hg	18" Hg	18" Hg	18" Hg	13" Hg	16" Hg	18" Hg	18" Hg	18" Hg	18" Hg
Filter Type / Micron Size	Certified HEPA Filtration Included											
S'HUSH SILENCER	76	77	78	77	78	77	76	77	78	80	78	80
Shipping Weight (lbs)	120	120	120	135	130	145	120	120	120	135	130	145

© Hafcovac

301 Greenwood Avenue, Midland Park, NJ 07432 Phone: 201.447.0433 | Fax: 201.447.1065 info@hafcovac.com